
| | ø 13.67 [.538] 13.31 [.524] |
|-----|------------------------------------|
| | ø 31.75 1.250 31.69 1.248 |
| | 16.1 [.63] 15.4 [.61] |
| | 42.0 [1.65] MAX COUPLING LENGTH |
| -B- | 48.6 1.91 45.9 1.81 |

NOTE

- 1 MOUNTING TYPE: OPTION AJ
- 2 DUTPUT SHAFT: DPTION 25

| RE∨ | DESCRIPTION | BY | DATE | ECN |
|-----|---------------------|-----|----------|--------|
| Α | ENGINEERING RELEASE | AAK | 02/20/06 | M66669 |
| В | REVISED | AAB | 07-06-10 | M79504 |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |





REVIEWED FOR CLASSIFICATION PER ESP-042

| UNLESS OTHER SPECIFIED A DIMENSIONS AR | LL | DF | RAWING E | BASED 0 | N | IZNA | Y14.5M-1 | 982 | | |
|--|-----------------------|---|---------------------------|---|-------|-----------|----------|---------|------|--|
| INCHES MILLIMETERS (INCHES) TOLERANC | | THE REPRODUCTION, DISTRIBUTION, AND UTILIZATION OF THIS DOCUMENT, AS WELL AS THE COMMUNICATION OF IT'S CONTENTS TO OTHERS WITHOUT EXPLICIT AUTHORIZATION IS PROHIBITED. OFFENDERS WILL BE HELD LIABLE FOR THE PAYMENT OF DAMAGES ALL RIGHTS RESERVED IN THE EVENT OF THE GRANT OF A PATENT. UTILITY MODEL, OR | | | | | | | | |
| .x ± | | DESIGN. (PER ISO 16016) | | | | | | | | |
| .xx ± REF .xxx ± ONLY | | BY/DATE CHECKED | AAK 2/21/06 AGJ | MATERIAL/HEA | T TR | EAT | | ' | | |
| UNSPECIFIEI RADII ARE | UNSPECIFIED RADII ARE | ENGRG | 2/21/06 JML 2/22/06 | TITLE 2000 SERIES MOTOR | | | | | | |
| | | METALLURGY BY/DATE | | SHAFT INSTALLATION | | | | | | |
| UNSPECIFIE DRAFT ANGLES | | O C | | MICROINCHES MICROMETERS (MICROINCHES) | ` | A-688-048 | | | | |
| B SIZE | | | T SCALE | ARITHMETICAL AV | ERAGE | SCALE | 1/1 | SHEET 1 | of 1 | |